

Bante 210/920 Benchtop pH/ORP Meter




Measurement Parameters

- Bante 210: pH, mV, temperature
- Bante 920: pH, mV, relative mV, temperature

Bante 210 Features

- 1 to 3 points calibration with automatic recognition for USA and NIST buffers
- Automatic electrode diagnosis helps user decide whether to replace the pH electrode
- Automatic temperature compensation ensures accurate readings over the entire range
- Auto-read function senses and locks the measurement endpoint
- Setup menu allows setting the pH buffer set, number of calibration points, temperature unit, etc.
- Reset function automatically resumes all settings back to the factory defaults



Bante 920 Features

pH

- 1 to 5 points calibration with automatic recognition for USA, NIST and DIN buffers
- Automatic electrode diagnosis shows the pH slope and zero offset
- Automatic temperature compensation ensures accurate readings over the entire range
- Calibration due alarm reminds the user to calibrate the meter regularly

ORP

- 1 point offset calibration allows adjusting the displayed value to a known standard
- Relative and absolute millivolt modes ensure the reliable ORP measurements

General Features

- Auto-read function senses and locks the measurement endpoint
- Setup menu allows setting the pH buffer set, number of calibration points, resolution, stability criteria, temperature unit, date and time, etc.
- Reset function automatically resumes all settings back to the factory defaults
- Expanded memory stores or recalls up to 500 data sets
- USB communication interface for data transfer and timed interval readings



Specifications

	Model	Bante 210	Bante 920
pH	Range	-1.00~15.00 pH	-2.000~20.000 pH
	Resolution	0.01 pH	0.001, 0.01, 0.1 pH, selectable
	Accuracy	±0.01 pH	±0.002 pH
	Calibration	1 to 3 points	1 to 5 points
ORP	pH Buffer Options	USA (4.01/7.00/10.01), NIST (4.01/6.86/9.18)	USA, NIST, DIN, 2 custom buffers
	mV Range	±1999 mV	±1999.9 mV
	Relative mV Range	—	±1999.9 mV
	Resolution	1 mV	0.1, 1 mV, selectable
	Accuracy	±1 mV	±0.2 mV
Temperature	Calibration	—	1 point
	Range	0~105°C/32~221°F	0~105°C/32~221°F
	Resolution	0.1°C/0.1°F	0.1°C/0.1°F
	Accuracy	±1°C/±1.8°F	±0.5°C/±0.9°F
Other Specifications	Offset Calibration	1 point, reading ±10°C	1 point, reading ±10°C
	Temperature Compensation	0~100°C, manual or automatic	0~100°C, manual or automatic
	Stability Criteria	—	Low or high
	Calibration Due Alarm	—	1 to 31 days or off
	Slope/Offset Display	—	Yes
	Hold Function	Manual or auto-endpoint	Manual or auto-endpoint
	Memory	—	500 data sets
	Communication Interface	—	USB
	Connector	BNC, 3.5 mm jack socket	BNC, 3.5 mm jack socket
	Display	Custom LCD (120×60 mm)	Custom LCD (125×100 mm)
	Power Requirements	9V DC power adapter	5V DC power adapter
	Dimensions	210(L)×205(W)×75(H) mm	210(L)×188(W)×60(H) mm
	Weight	1.5 kg	1.5 kg

Ordering Information

- Bante 210/920-CN: Meter, E201-BNC plastic-body pH electrode, temperature probe, pH buffer reagents, electrode holder, USB cable (for Bante920 only), power adapter
- Bante 210/920-UK: Meter, P11 glass pH electrode, temperature probe, pH buffer reagents, electrode holder, USB cable (for Bante920 only), power adapter
- Bante 920-ORP: Meter, E201-BNC plastic-body pH electrode, 501 ORP electrode, temperature probe, pH buffer reagents, electrode holder, USB cable, power adapter